

Product technical sheet

RECYCLED RC1497







3 - 12 years

14 kids

37,0 m²



Material specification

- The structure is made of a durable, moisture-resistant and low-temperature recycled composite,
- Hot-dip galvanized and powder coated or powder galvanized and powder coated or stainless steel construction elements,
- The covers are made of recycled HDPE panel, resistant to weather conditions
- Attested, safe seats,
- Calibrated stainless steel chains, preventing fingers entrapment,
- Stainless steel swing fittings,
- Screws covered with plastic caps and/or stainless steel screws,



Facilitating disability



easy access



integration



Physical development




rest





rocking











Product technical sheet

RECYCLED RC1497

Product data

Length	195 cm	
Width	575 cm	
Total height	240 cm	
Age group	3 - 12 years	
Number of users	14 kids	
Safety zone	37,0 m2	
Free fall height	130 cm	
In accordance with norm EN	1176-1:2017+A1:2023	
Weight of the heaviest part	15 kg	
Dimensions of the largest part	300x9x9 cm	
Availability of spare parts	YES	
Installation time	2 h	

Data is subject to change without prior notice.

Additional information

- equipment adapted for the disabled; intended for public playgrounds;
- equipment has a certificate issued by an accredited entity or a declaration of conformity;
- no sharp edges or chinks that would pose a danger of jamming the head, fingers or any other body parts;
- anchoring on flat surface, 80/70/60 cm deep;
- render is for reference only, the actual appearance of the equipment and its color may vary;

Guarantee



30 year guarantee -Structural strength of steel and stainless steel components



15 year guarantee -Structural failure of steel and stainless steel, for dynamic equipment



10 year guarantee - Structural failure of high density polyethylene and high pressure laminates components



5 year guarantee - Corrosion of stainless steel and hot dip galvanized and powder coated components; against bark beetles and rot in case of wooden structural elements

 $\label{eq:decomposition} \mbox{ Detailed information in the guarantee card }$



VAT: 534-250-14-46 PHONE: +48 42 203 24 99 ext. 26 M: +48 793 404 991





Surfaces according to EN 1176-1:2017+A1:2023

	Description (mm)	Layer thickness (cm)	Maximum fall heights (cm)
Turf/ top layer of soil (A,B,C)	-	-	≤100
bark (A.C.)	C) Particle size from 20 to 80	30	≤200
bark (A,C)		40	≤300
woodchips (A,C)	Particle size from 5 to 30	30	≤200
		40	≤300
sand or gravel (A,C)	Particle size from 0,25 to 8	30	≤200
		40	≤300
synthetic attested (A,B,C)	Tested according to EN 1177		130

Product technical sheet

RECYCLED RC1497

Amount of safe surface corresponding with free fall height:

HIC 130 37,0 m²

Data is subject to change without prior notice.

